

OD = Outside Dia ID = Inside Dia		
Inches	OD	NB(Normal Bore)
½"	21.3 mm	15
¾"	26.7 mm	20
1"	33.4 mm	25
1 ½"	48.26 mm	40
2"	60.3 mm	50
2 ½"	73.2 mm	
3 "	88.9 mm	80
3 ½"	101.8 mm	

4"	114.3 mm	100
5"	141.3 mm	125
6"	168.3 mm	150
8"	219.1 mm	200
10"	273.1 mm	250
12"	323.9 mm	300
14" x25.4	355.6 mm	350
16" x25.4	406.4 mm	400
18" x25.4	457.2 mm	450
20" x25.4	508 mm	500
22" x25.4	558.8 mm	550
24" x25.4	609.6 mm	600

OD	OD X CF	OD VALUE x CF	TOTAL CF
1"	1" x 3.142	1" OD=33.4 X 3.142	105 mm
2"	2" x 3.142	2" OD= 60.3 X 3.142	189 mm
3"	3" x 3.142	3" OD=88.9 X 3.142	279 mm
4"	4" x 3.142	4" OD=114.3 X 3.142	359 mm
6"	6" x 3.142	6" OD=168.3 X 3.142	528 mm
8"	8" x 3.142	8" OD=219.1 X 3.142	688 mm
10"	10" x 3.142	10" OD=273.1 X 3.142	858 mm
12"	12" x 3.142	12" OD=323.9 X 3.142	1017 mm
14"	14" x 3.142	14" OD=355.6 X 3.142	1117 mm
16"	16" x 3.142	16" OD=406.4 X 3.142	1277 mm
18"	18" x 3.142	18" OD=457.2 X 3.142	1436 mm
20"	20" x 3.142	20" OD=508 X 3.142	1596 mm
Formula → OD x 22/7 22/7= 3.142			