

Y Strainer Size					
Nominal Size	Nominal Size (Inch)	F ±2	D	T	H
25	1	140	120.7	12.7	110
32	1 1/4	155	133.5	15.9	120
40	1 1/2	165	139.7	15.9	140
50	2	185	165.1	19.1	160
65	2 1/2	206	184.2	19.1	180
80	3	255	203.2	19.1	210
100	4	295	228.6	22.2	255
125	5	350	279.4	25.4	285
150	6	385	304.8	25.4	310
200	8	475	368.3	28.6	415
250	10	560	431.8	28.6	500
300	12	660	489	31.8	600

Gate Valve Size Chart

Size (Inches)	Face-to-Face (mm)	Flange OD (mm)	Bolt Hole Dia. (mm)	No. of Bolt Holes	Height (mm) (Approx.)
1/2"	108	90	15	4	150-200
3/4"	117	100	16	4	170-220
1"	127	110	16	4	200-250
1-1/2"	165	125	18	4	250-300
2"	178	150	19	4	300-350
2-1/2"	190	180	19	4	350-400
3"	203	190	19	4	400-450
4"	229	230	19	8	450-500
6"	267	280	22	8	600-700
8"	292	345	22	8	750-850
10"	330	405	25	12	900-1000
12"	356	485	25	12	1000-1200

<b>NRV (Non-Return Valve) Size Chart</b>				
<b>Size (Inches)</b>	<b>End Connection</b>	<b>A (Face-to-Face) mm</b>	<b>B (Height) mm</b>	<b>Pressure Rating (Class)</b>
<b>1/2"</b>	<b>Threaded / Flanged</b>	<b>80-100</b>	<b>60-80</b>	<b>150 / 300 / 600</b>
<b>3/4"</b>	<b>Threaded / Flanged</b>	<b>100-120</b>	<b>70-90</b>	<b>150 / 300 / 600</b>
<b>1"</b>	<b>Threaded / Flanged</b>	<b>120-150</b>	<b>90-120</b>	<b>150 / 300 / 600</b>
<b>1-1/2"</b>	<b>Threaded / Flanged</b>	<b>150-180</b>	<b>120-140</b>	<b>150 / 300 / 600</b>
<b>2"</b>	<b>Flanged</b>	<b>180-220</b>	<b>150-180</b>	<b>150 / 300 / 600</b>
<b>3"</b>	<b>Flanged</b>	<b>220-280</b>	<b>200-250</b>	<b>150 / 300 / 600</b>
<b>4"</b>	<b>Flanged</b>	<b>280-350</b>	<b>250-300</b>	<b>150 / 300 / 600</b>
<b>6"</b>	<b>Flanged</b>	<b>350-450</b>	<b>350-400</b>	<b>150 / 300 / 600</b>
<b>8"</b>	<b>Flanged</b>	<b>450-550</b>	<b>400-500</b>	<b>150 / 300 / 600</b>
<b>10"</b>	<b>Flanged</b>	<b>550-650</b>	<b>500-600</b>	<b>150 / 300 / 600</b>
<b>12"</b>	<b>Flanged</b>	<b>650-750</b>	<b>600-700</b>	<b>150 / 300 / 600</b>